

SEE TYPICAL SECTION - PEDESTRIAN BARRIER FOR ADDITIONAL DETAILS

THE CONTRACTOR IS ADVISED THAT THE SLIPFORM CONSTRUCTION

METHOD IS A PATENTED PROPRIETARY PROCESS FOR BARRIERS


JUNCTION BOX LOCATIONS

STATION OFFSET "TS" OR "LT"

TS = TRAFFIC SYSTEM LT = LIGHTING SYSTEM


JUNCTION BOX LOCATIONS SHOWN ARE APPROXIMATE. CENTER JUNCTION BOX INSTALLATION BETWEEN BARRIER DUMMY JOINTS.


INSTALL ALL CONDUIT RUNS TO DRAIN TO A BRIDGE END OR PROVIDE DRAIN AT ALL LOW POINTS IN CONDUIT RUN ON BRIDGE.






SIDEWALK REINFORCING STEEL NOT SHOWN FOR CLARITY.







WITH A FRACTURED FIN FINISH.


FRACTURED FIN FINISH






FOR DETAILS NOT SHOWN SEE "OUTSIDE ELEVATION" AND "TYPICAL SECTION ~ PEDESTRIAN BARRIER"





FOR DETAILS NOT SHOWN SEE "OUTSIDE ELEVATION" AND "TYPICAL SECTION ~ PEDESTRIAN BARRIER"

* BLOCKOUT WIDTH MAY BE INCREASED TO 6" TO ALLOW CONDUITS OF A LARGER DIAMETER THAN 2" TO EXIT BARRIER OR WALL WITHOUT REBAR STEEL CONFLICT



- 3" x 10" x 2'-0" BLOCKOUT IN WALL TO ALLOW CONDUITS TO EXIT, BACKFILL WITH GROUT *

— 2 ~ 2"Ø CONDUIT PIPES OR SEE WIRING SCHEDULE FOR CONDUIT SIZE

SECTION B WALL

DETAIL FOR RETAINING WALL OR WINGWALL. FOR REINFORCING NOT SHOWN SEE STD. PLAN D-15 OR WINGWALL PLANS.

		CON CITINDTIKE DECK TITIOKI	HOTIKO DEOK THIOKHEOD.								
2	Bridge Design Engr,	M:\ST,	ANDARDS\IPattic Rarricks\Pdocto	العلا	3arrier	IPED I	D BARRIER 2.MAN				
7	Supervisor		_			REGION NO.	STATE	FED, AID PROJ, NO,	SHEET NO.	TOTA SHEET	
ī	Designed By					10	WASH,				
	Checked By										
ξ'	Detailed By					JOBI	NUMBER				
	Bridge Projects Engr.										
	Prelim. Plan By										
	Architect/Specialist	DATE	REVISION	BY	APP'D						

BRIDGE AND STRUCTURES OFFICE



STANDARD
TRAFFIC BARRIERS

PEDESTRIAN BARRIER
DETAILS 2 OF 3

10.2-A4-2

Tue May 08 08:06:55 2012